



SHELDONS ENGINEERING INC

REQUEST FOR QUOTATION

(t) 800.265.3572 (f) 905.564.9004 sales@sheldonsengineering.com

Date/Time Field

CONTACT NAME

COMPANY & LOCATION

BUS. TELEPHONE

BUS. FAX

EMAIL

FAN APPLICATION

- HVAC
- Industrial Process
- Food and Beverage Process
- Pharmaceutical Process
- Material Handling or Heavy Industrial Process
- Conveyed mat'l
- lb/hr
- Centrifugal Fan
- Tube or Vane Axial Fan
- Roof Top Axial Fan
- Wall Propellor Fan
- Inline Centrifugal Fan
- Mixed Flow Fan
- Plenum Fan
- Plug Fan

INLET GAS PROPERTIES

- Clean Air
- Gas Mixture (indicate density)
- density lb/ft³

SOUND PROPERTIES

- INLET SILENCER
- INSULATION PINS
- OUTLET SILENCER
- ATTENUATION
- Max dBA @ 5ft

PERFORMANCE

Flow acfm Inlet Gas Temp deg F.

Inlet Static P. in.w.c. Max. Motor HP

Outlet Static P. in.w.c. Max. RPM

NOTES

ARRANGEMENT

- Direct Drive Fan
- Belt Drive Fan
- Arrangement
- Single Width, Single Inlet
- Double Width, Double Inlet
- Motor Position
- Discharge and Rotation (Fig#)
- see attached files for Reference

MOTOR & ACCESSORIES

- Sheldons to Supply and Mount Motor & Drives
- Customer to Supply and Mount Motor & Drives
- No Motor and Drives
- Sheldons to Supply/Mount Drives on Customer's Motor
- Voltage
- Hazardous
- Haz. Groups
- Add Fused Disconnect to Fan
- Add Non-Fused Disconnect Switch

ACCESSORIES

- Punched Flanged Inlet
- Slip Fit Inlet
- Punched Flange Outlet
- Slip Fit Inlet
- Housing Drain
- Inlet Box(s)
- Housing Access Door
- Extended Lube Lines
- Outlet Cowl
- Backdraft Damper
- Shaft Seal
- Inlet Screen
- Split Housing
- AMCA Spark
- Material